

Vollkunststoff-Wellschlauch

Innen und außen gewellt als Kabelsammler für große Kabelmengen

Material

ROHRflex® Multi - PA 6 / PA 6
ROHRflex® Multi - PA 12 / PA 12

Eigenschaften

- Trittfest
- flüssigkeitsdicht
- flammwidrig
- HB nach UL 94 (Multi PA 6)
- V2 nach UL 94 (Multi PA 12)

ROHRflex® Multi-PA 6

- Ölbeständig bis +80° C
- benzinbeständig
- weitgehend säure- und lösungsmittelbeständig

ROHRflex® Multi-PA 12

- Öl- und benzinbeständig
- weitgehend säure- und lösungsmittelbeständig
- besonders geeignet bei häufigem Biegewechsel

Corrugated all-plastic tubing

Internally and externally corrugated, as cable buncher for large quantity of cables

Material

ROHRflex® Multi - PA 6 / PA 6
ROHRflex® Multi - PA 12 / PA 12

Properties

- Non-crush
- liquid-tight
- flame retarding
- HB acc. to UL 94 (Multi PA 6)
- V2 acc. to UL 94 (Multi PA 12)

ROHRflex® Multi-PA 6

- Oil resistant up to +80°C
- benzine resistant
- highly resistant to acids and solvents

ROHRflex® Multi-PA 12

- Oil and benzine resistant
- widely resistant to acids and solvents
- especially suitable for applications with frequently reversed bending cycles



Leichte Montage der Anschlusssteile durch Vorarretierung des Verschlusses





Easy mounting with pre-locking mechanism

Anwendungsgebiete

- Maschinen- und Anlagenbau
- Fahrzeugbau
- Schienenfahrzeuge
- Schiffsbau
- Automation
- Elektroanlagen

Application

- Machine and Plant Constructions
- Automotive
- Railway Industry
- Shipbuilding
- Automation
- Electrical Installations

FLEXA No.	FLEXA No.	LW ID				
grau grey	schwarz black	∅	mm	stat dyn	kg/m	m
ROHRflex® Multi-PA 6						
0206.201.056	0206.202.056	56	56,3 x 67,2	130 270	0,35	10
0206.201.070	0206.202.070	70	66,5 x 79,2	170 350	0,46	10
0206.201.095	0206.202.095	95	91,0 x 106,0	225 450	0,79	10
ROHRflex® Multi-PA 12						
0207.201.056	0207.202.056	56	56,3 x 67,2	130 270	0,35	10
0207.201.070	0207.202.070	70	66,5 x 79,2	170 350	0,46	10
0207.201.095	0207.202.095	95	91,0 x 106,0	225 450	0,79	10



ROHRflex® Multi-PA 6